



SINGLE ACTING STEEPLE CYLINDER SPECIFICATIONS

BORE (in)	FLG (in-class)	CE CLR (%)	HE CLR (%)	VALVE		CE CS	HE CS	VALVE VELOCITY		MAWP
		BASE	BASE	model (no)	area (in ²)	% (additional) % / SPACER	% (additional) % / SPACER	CE	HE	(psig)
10	6-150	12.5	MATCH 5 or 4 1/2 HE	(2) 105CRO	11.38	20	5	7056		200
9.5		13.5				25		6.25	6359	
8	4-300	13.5		105CRO	5.69	20	5	7750		300
7.5		14.5				25	6.25	6833		
7	4-300	15.5	MATCH 4 or 3 1/2 HE	105CRO	5.69	20	5	5931		300
6.5		17.5				25	6.25	5090		
6	3-300	18	MATCH 3 or 2 1/2 HE	88CRO	3.77	20	5	6513		500
5.5		19.5				23	5.75	5431		
5	2 1/2-600	20		70CRO	2.67	20	5	7015		1000
4.5		22	25			5.5	5605			
5	2 1/2-600		20	70CRO	2.67		15	5	7392	1000
4.5			22			15	5	5979		
4	2-600		20	60CRO	Suction 2.05		15	5	6343	1000
3.5			23		Discharge 1.64		15	5	4743	
3	1 1/2-1500		25	42CRO	Suction 1.08		15	5	6817	1500
2.5			29		Discharge 0.87		15	5	4387	

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE